



MODEL #	DESCRIPTION
JB3.0-481	Single Connector Charger
JB3.0-482	Dual Connector Charger

CERTIFICATIONS
TUV Rheinland UL 2231-1, UL 2231-2, UL 2594
ENERGY STAR- Single and Double Connectors

AC INPUT
Voltage: 208/240 VAC
Breaker: Rating 60A
Single Connector: 3 Wire (L1,L2 & G)
Double Connector: 5 Wire (L1, L1, L2, L2 & G)

AC OUTPUT PER CONNECTOR
11.5 kW at 240VAC
10kW at 208VAC

CHARGE TIME FOR AVERAGE EV WITH 80 kWh CAPACITY GOING FROM 20-80%
4.2 Hours

OPERATING TEMPERATURE
- 20° C to +50° C
- 4° F to +122° F

COMMUNICATIONS
Cellular
Ethernet

DIMENSIONS
71.25" Total Height with Pedestal
36.5" Total Height w/out Pedestal
16" Width Without Connectors
12" Depth

CORD LENGTH
18 feet

PROTOCOL
OCPP 1.6J

CONNECTORS
SAE J1772 Type 1

ENCLOSURE
Type 3R Aluminum

OPTIONS
Wall Bracket
Pedestal Mount
Branded Door Graphics

USER INTERFACE
LED Indicators
RFID Card Reader