



TELLUS POWER GREEN

# TELLUS POWER GREEN DC FAST CHARGER 160kW Series

## FEATURES

- DCFC and HPC System with 1000VDC
- Powerful Compact All-In-One Charger
- Simple Air-Cooled Power Modules
- Easy to Maintain
- Parallel Charging Feature
- Liquid Cooled Cables
- OCPP 1.6
- Credit Card Reader
- Cord Management



## Tellus Power Green DC Fast Charger Specifications



Product Number	TP5-160-480	HPC-160-480
Input Voltage	480V (3P + N + PE), 60Hz	
Output Voltage	150–1000 VDC	
Max Output Current	Up to 200A per Connector	Up to 400A per Connector
FLA    Breaker Rating	215A    300A	
Power Factor	>0.98	
Efficiency	>94% at nominal output power	
Connector Options	CCS1 and CCS1 CCS1 and CHAdeMO	CCS1 CCS1 and CCS1 CCS and CHAdeMO
CHAdeMO Cable	125A (Standard) Or 200A	
CCS Cable	200A	400A Liquid Cooled
Charging Protocol Standards	Mode 4, IEC-61851, ISO-15118, DIN 70121    Mode 4, CHAdeMO 0.9, 1.0	
Cycle Mode	1 x 160kW (Max : 200A)	1 x 160kW (Max : 400A)
Parallel Mode	2 x 80kW	2 x 80kW
Connector cable length	CCS – 16ft (5m) CHAdeMO – 16ft (5m)	CCS – 13ft (4m) CHAdeMO– 16ft (5m)
Cable Management	Included	Included
Weight	880 lbs (400 kg)	950 lbs (430 kg)
Dimensions (L x D x H)	29.5" x 26.5" x 73"	
Insulation (input – output)	>2.5 kV	
Ingress Protection	NEMA 3S (IP54), IK10	
Operating Temperature	-22°F to 131°F (-30°C to 55°C )	
Altitude	< 6600ft (2000m)	
Working    Storage Humidity	≤ 95% RH    ≤ 99% RH (Non-condensing)	
Display	10" touch screen	
Communication    Protocol	Ethernet, 4G/WiFi    OCPP 1.6J	
Access Control	RFID : ISO/IEC 14443A/B   Credit Card Reader (Optional)	
Metering	DC kWh meter per each connector	
Power Electronics Cooling	Air Cooled	
Electrical Safety: GFCI	RCD 20 mA Type A	
Electrical Safety: Surge Protection	20 kA	
Electrical Safety General	Over Voltage, Under Voltage, Over Current, Missing Ground	
Electrical Safety: Output Short	Output power disabled when output is short circuited	
Electrical Safety Temperature	Temperature Sensors @ Charge Coupler and Power Electronics	
Emergency Stop	Disables output power with emergency stop button	
Regulatory Compliance	UL-2202    EMC: EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012	